Screens » Desking Screens



Collection: Bilby









IRONBARK - TIMBER PET



MERBAU - TIMBER PET



SPOTTED GUM -TIMBER PET

Screens » Desking Screens



Bilby Desking Screen Extension extends the height of an existing desking screen. It's ideal when you want to add extra privacy or noise absorption.

Description

Bilby panel topper is ideal for when you want to create extra privacy or noise absorption. The extra 12" height is available in 6 widths from 23.5" to 71.5", catering for narrow and wide desking alike. The sustainable PET is available in 24 colors and 4 wood prints so you can match the screen that's already there, or create a visual contrast

func., Bilby Desking Screens are easily cleaned with bleach and water.

Made In

USA

Dimensions

- 23.5" (597mm) w x 12" (305mm) h x 3" (77mm) d
- 35.5" (902mm) w x 12" (305mm) h x 3" (77mm) d
- 41.5" (1055mm) w x 12" (305mm) h x 3" (77mm) d
- 47.5" (1207mm) w x 12" (305mm) h x 3" (77mm) d
- 59.5" (1512mm) w x 12" (305mm) h x 3" (77mm) d
- 71.5" (1817mm) w x 12" (305mm) h x 3" (77mm) d



Powder Coat	White ONLY
PET Colours	 24 Colors – Bark, Brick, Cadet, Chambray, Cobalt, Ecru, Fossil, Frost, Grass, Greige, Ivory, Linen, Malachite, Mandarin, Midnight, Ochre, Olive, Pebble, Pewter, Sky, Slate, Smoke, Sunshine, Tar. 4 Timber Prints – Eucalyptus, Iron bark, Merbau, Spotted Gum.
Composition	Density 0.5 lb/ft² 2.4 kg /m²
Material	 60% post-consumer recycled PET bottles. 35% pre-consumer recycled content from PET chips 5% bio-based Polylactic Acid (PLA)
Fire Rating	ASTM-E84 – Class A classification AS ISO 9705 – 2003 – Group 1 classification EN-13501 – B-s2-d0 classification
Warranty	5-year warranty.
Lead Time	4 weeks
Assembly & Delivery	Flat pack delivery, minimal assembly required. See installation instructions for detail.
How to Specify	• Select 1 x PET Color



Care Instructions	Dab func. with a damp clean cloth and mild solution of liquid detergent and warm water. Repeat using only clean water, then pat dry with a lint free cloth.
	For difficult stains, use a solution of household bleach (10% bleach / 90% water).
	To remove the bleach, repeat using a clean, water dampened cloth, then pat dry.
	Always test in an inconspicuous area first and if you don't see the expected results, contact us.
Additional Comments	To see how vivid the colors truly are, it's easy to request a sample through the "Request information" button on this page, or you can ask for one from your local sales guru.
Inclusions	Add-on shell clamp brackets, PET panels

